



Highlights

- 2 to n poles
- 1 pole module
- Push-In connection
- Spacing 7.5 mm
- Wire entry vertical to PCB
- With two soldering pins
- 24 A with 2.5 mm² wire
- 15 different colors available

Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2 mm ²
Stranded (flexible) max	2.5 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	2.5 mm ²

Dimensions

Stripped length	10.0 mm
PCB hole diameter	1.1 mm

Materials

Solder tab	Copper Alloy
Clamp spring	Stainless Steel

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Operating temperature (without mech. load)	-40 °C - 105 °C
Store temperature	-40 °C - 105 °C

Spacing 7.5 mm

Wave Soldering Process

Soldering temperature, recommended	260 °C
Peak soldering time, recommended	3-4 s

Reflow Process

Soldering temperature, recommended	-
Peak soldering time, recommended	-

Colours

BASALT GREY, RAL 7012
LIGHT GREY, RAL 7035
TRAFFIC GREY, RAL 7042
BLACK, RAL 9011
LIGHT GREEN, similar RAL 6018
GREEN, RAL 6018
GREEN/YELLOW, RAL 6018 - 1018/5
RED, RAL 3003
ORANGE, RAL 2011
BLUE, RAL 5015
WHITE, RAL 9003

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.

Ratings

					
UseGroup	B	C	D		
Rated voltage	300 V	150 V	300 V	250 V	
Rated current	20 A	20 A	10 A	24 A	
Overvoltage category				III	
Rated wire size				min	max
- solid	AWG 24-12	AWG 24-12	AWG 24-12	0.2 mm²	2.5 mm²
- stranded	AWG 24-12	AWG 24-12	AWG 24-12	0.2 mm²	2.5 mm²
Test voltage	1.60 kV	1.30 kV	1.60 kV	3.0 kV	

Accessoires

Figure	Designation	Article Number
	Spacer SPC-AK4200-baGY	Order Data: 54200000000
	Side Wall with Coding Pin SW-AK4200-CP-V-baGY	Order Data: 54200000001



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // AK4200/..-7.5-V-BAGY

Spacing 7.5 mm

Order Data (Spacing 7.5 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	13.90	AK4200/2-7.5-V-baGY	54200020521 D	50
3	21.40	AK4200/3-7.5-V-baGY	54200030521 D	50
4	28.90	AK4200/4-7.5-V-baGY	54200040521 D	50
5	36.40	AK4200/5-7.5-V-baGY	54200050521 D	50
6	43.90	AK4200/6-7.5-V-baGY	54200060521 D	50
7	51.40	AK4200/7-7.5-V-baGY	54200070521 D	50
8	58.90	AK4200/8-7.5-V-baGY	54200080521 D	50
9	66.40	AK4200/9-7.5-V-baGY	54200090521 D	50
10	73.90	AK4200/10-7.5-V-baGY	54200100521 D	50
11	81.40	AK4200/11-7.5-V-baGY	54200110521 D	50
12	88.90	AK4200/12-7.5-V-baGY	54200120521 D	50

Technical drawing

