PTR HARTMANN
A Phoenix Mecano Company



Highlights	
2 to 12 poles	
2 and 3 pole modules	
Spacing 5.0 mm	
Lift type	
Wire entry vertical to PCB	
24 A with 2.5 mm² wire	
Wire Sizes	
Solid min	0.2 mm²
Solid max	4.0 mm²
Stranded (flexible) min	0.2 mm²
Stranded (flexible) max	2.5 mm²
Stranded with ferrule min	0.25 mm²
Stranded with ferrule max	2.5 mm²
Dimensions	
Stripped length	8.0 mm
PCB hole diameter	1.3 mm
Materials	
Clamp	Brass
Screw	Steel
Solder tab	Copper Alloy
Insulating Material	
Material	PA 6.6
Flammability class	UL 94 V-0
Temperatures	
Operating temperature (without mech. load)	-40 °C - 105 °C
Store temperature	-40 °C - 105 °C
Wave Soldering Process	
Soldering temperature, recommended	260 °C
Peak soldering time, recommended	3-4 s

Spacing 5.0 mm

Reflow Process

Soldering temperature, recommended	-
Peak soldering time, recommended	-

Colours

GREEN, RAL 6018

GREY, RAL 7016

PEBBLE GREY, RAL 7032

BLUE, RAL 5015


LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.

Ratings

	c UL us			VDE	
UseGroup	B	C	D		
Rated voltage	300 V	-	300 V	250 V	
Rated current	15 A	-	10 A	24 A	
Rated wire size				min	max
- solid	AWG 30-12	-	AWG 30-12	0.5 mm²	4.0 mm²
- stranded	AWG 30-12	-	AWG 30-12	0.5 mm²	2.5 mm²
Torque	0.45 Nm	-	0.45 Nm	0.50 Nm	
Screw size	M3	-	M3	M3	
Test voltage	1.60 kV	-	1.60 kV	2.0 kV	

Accessoires

Figure	Designation	Article Number
	Bridge, 2-pole, insulated, BRI/2-5.0/5.08-LIGHT GREY	Order Data: 50000000006
	Bridge, 3-pole, insulated, BRI/3-5.0/5.08-LIGHT GREY	Order Data: 50000000007
	Bridge, 2-pole, BR/2-5.0/5.08-L7.0	Order Data: 50000000008
	Screw Cover SC-AK700-YELLOW	Order Data: 50700000004

PTR HARTMANN
A Phoenix Mecano Company

Spacing 5.0 mm

Order Data (Spacing 5.0 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	10.60	AK700/2-5.0-H-GREEN	50700020261 F	200
3	15.60	AK700/3-5.0-H-GREEN	50700030261 F	200
4	20.60	AK700/4-5.0-H-GREEN	50700040261 F	200
5	25.60	AK700/5-5.0-H-GREEN	50700050261 F	200
6	30.60	AK700/6-5.0-H-GREEN	50700060261 E	100
7	35.60	AK700/7-5.0-H-GREEN	50700070261 E	100
8	40.60	AK700/8-5.0-H-GREEN	50700080261 E	100
9	45.60	AK700/9-5.0-H-GREEN	50700090261 E	100
10	50.60	AK700/10-5.0-H-GREEN	50700100261 D	50
11	55.60	AK700/11-5.0-H-GREEN	50700110261 D	50
12	60.60	AK700/12-5.0-H-GREEN	50700120261 D	50

Technical drawing

