



Highlights

2 to 8 poles

1 and 2 pole modules

Spacing 10.16 mm

Lift type

Wire entry parallel to PCB

Max. 1.000 V

Wire Sizes

Solid min 0.14 mm²

Solid max 2.5 mm²

Stranded (flexible) min 0.14 mm²

Stranded (flexible) max 1.5 mm²

Stranded with ferrule min 0.25 mm²

Stranded with ferrule max 1.5 mm²

Dimensions

Stripped length 6.0 mm

PCB hole diameter 1.3 mm

Materials

Clamp Brass

Screw Steel

Solder tab Brass

Insulating Material

Material PA 6.6

Flammability class UL 94 V-0

Temperatures

Operating temperature (without mech. load) -40 °C - 105 °C

Store temperature -40 °C - 105 °C

Wave Soldering Process

Soldering temperature, recommended 260 °C

Peak soldering time, recommended 3-4 s

Spacing 10.16 mm

Reflow Process

Soldering temperature, recommended -

Peak soldering time, recommended -

Colours

GREEN, RAL 6018

LIGHT GREY, RAL 7035

BLUE, RAL 5015

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.

Ratings

					
UseGroup	B	C	D		
Rated voltage	300 V	150 V	300 V	1.000 V	
Rated current	15 A	15 A	10 A	17.5 A	
Rated wire size				min	max
- solid	AWG 22-12	AWG 22-12	AWG 22-12	0.5 mm ²	2.5 mm ²
- stranded	AWG 22-12	AWG 22-12	AWG 22-12	0.5 mm ²	1.5 mm ²
Torque	0.50 Nm	0.50 Nm	0.50 Nm	0.50 Nm	
Screw size	M3	M3	M3	M3	
Test voltage	1.60 kV	1.30 kV	1.60 kV	3.5 kV	

Order Data (Spacing 10.16 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	15.84	AKZ350/2-10.16-V-GREEN	50350020021 F	200
3	26.00	AKZ350/3-10.16-V-GREEN	50350030021 F	200
4	36.16	AKZ350/4-10.16-V-GREEN	50350040021 E	100
5	46.32	AKZ350/5-10.16-V-GREEN	50350050021 E	100
6	56.48	AKZ350/6-10.16-V-GREEN	50350060021 D	50
7	66.64	AKZ350/7-10.16-V-GREEN	50350070021 D	50
8	76.80	AKZ350/8-10.16-V-GREEN	50350080021 D	50
9	86.96	AKZ350/9-10.16-V-GREEN	50350090021 D	50
10	97.12	AKZ350/10-10.16-V-GREEN	50350100021 D	50
11	107.28	AKZ350/11-10.16-V-GREEN	50350110021 D	50
12	117.44	AKZ350/12-10.16-V-GREEN	50350120021 D	50



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // AKZ350/..-10.16-V-GREEN

Spacing 10.16 mm

Technical drawing

