

Highlights

2 to 6 poles

Spacing 15.24 mm

Lift type

Wire entry parallel to plugging direction

Coding with coding star

With snap-in hooks to snap onto the pin strip

Max. 630 V

Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2 mm ²
Stranded (flexible) max	2.5 mm ²
Stranded with ferrule min	0.25 mm ²
Stranded with ferrule max	2.5 mm ²

Dimensions

Stripped length	6.0 mm
-----------------	--------

Materials

Clamp	Brass
Screw	Steel
Contact spring	Bronze

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Operating temperature (without mech. load)	-40 °C - 105 °C
Store temperature	-40 °C - 105 °C

Wave Soldering Process

Soldering temperature, recommended	-
Peak soldering time, recommended	-

Spacing 15.24 mm

Reflow Process

Soldering temperature, recommended -

Peak soldering time, recommended -

Colours

LIGHT GREY, RAL 7035

GREEN, RAL 6018

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
 Special colours on request.

Ratings

					
UseGroup	B	C	D		
Rated voltage	600 V	600 V	-	630 V	
Rated current	15 A	15 A	-	12 A	
Overvoltage category				III	
Rated wire size				min	max
- solid	AWG 22-12	AWG 22-12	-	0.5 mm ² (5 A)	2.5 mm ² (12 A)
- stranded	AWG 22-12	AWG 22-12	-	0.5 mm ² (5 A)	2.5 mm ² (12 A)
Torque	0.80 Nm	0.80 Nm	-	0.50 Nm	
Screw size	M3	M3	-	M3	
Test voltage	2.20 kV	2.20 kV	-	6.0 kV	
Pollution degree				3	


Counterparts (Spacing 15.24 mm)

Pin Strip

STLZ960

In combination of connectors with different admission data, the lower value is valid.

Accessoires

Figure	Designation	Article Number
	Coding Star CS1-5.0/5.08-RED	Order Data: 50000000021
	Series AK(Z)960 with Separating Element	Order Data: on request
	Series AKZ960 with pull relief	Order Data: on request



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // AKZ960/..-15.24-GREEN

Spacing 15.24 mm

Order Data (Spacing 15.24 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	20.86	AKZ960/2-15.24-GREEN	50960020061 D	50
3	36.10	AKZ960/3-15.24-GREEN	50960030061 D	50
4	51.34	AKZ960/4-15.24-GREEN	50960040061 D	50
5	66.58	AKZ960/5-15.24-GREEN	50960050061 D	50
6	81.82	AKZ960/6-15.24-GREEN	50960060061 D	50

Technical drawing

