




PTR HARTMANN

A Phoenix Mecano Company

Technical Data // FR2.5-DRL

Push-In Type | Through Terminal Block
4 Connections



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	2.5 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions

Stripped length	12.0 mm
Width	5.1 mm
Length	77.7 mm
Height TS35 x 7.5	43.0 mm

ELECTRICAL DATA

General

Cross connection channels	2
---------------------------	---

COLOURS

	RED, similar RAL 3001
	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015
	ORANGE, similar RAL 2003
	GREEN, similar RAL 6018
	YELLOW, similar RAL 1023


**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // FR2.5-DRL

Push-In Type | Through Terminal Block

4 Connections

CONNECTION DIAGRAM**ORDER DATA**

Article Designation	Article Number	PU
FR2.5-DRL-BEIGE	43212.2	100
FR2.5-DRL-BLUE	43212.5	100
FR2.5-DRL-ORANGE	43212.3	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate FAP2.5/4A	493412.2	20
Cross-Connection insulated FQI2.5/2	493462.8	50
Cross-Connection insulated FQI2.5/3	493463.8	50
Cross-Connection insulated FQI2.5/4	493464.8	20
Cross-Connection insulated FQI2.5/5	493465.8	20
Cross-Connection insulated FQI2.5/6	493466.8	20
Cross-Connection insulated FQI2.5/7	493467.8	20
Cross-Connection insulated FQI2.5/8	493468.8	10
Cross-Connection insulated FQI2.5/9	493469.8	10
Cross-Connection insulated FQI2.5/10	493460.8	10
Four-Way Covers FAD2.5/4/B	493426.8	20
End Stopn ZES35/2	493811.2	50
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage	600 V	600 V	800 V
Rated current	21 A	21 A	24 A
Rated wire size	AWG 26-12	AWG 26-12	2.5 mm ²
Rated impulse voltage			8 kV
Pollution degree			3