



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // FRSL1.5

Push-In Type | Protective Conductor Clamp
2 Connections



Wire Sizes

Solid min	0.2 mm ²
Solid max	1.5 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	1.5 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	1.5 mm ²
Clamping range min	0.2mm ²
Clamping range max	1.5 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions


Stripped length	12.0 mm
Width	4.1 mm
Length	48.5 mm
Height TS35 x 7.5	43.0 mm

ELECTRICAL DATA

General

Cross connection channels	2
---------------------------	---

COLOURS



GREEN/YELLOW



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // FRSL1.5

Push-In Type | Protective Conductor Clamp

2 Connections

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
FRSL1.5-GREEN/YELLOW	43203.2	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate FAP1.5-4/2A	493400.2	20
Four-Way Covers FAD1.5/4/B	493425.8	20
End Stopn ZES35/2	493811.2	50
Quick Labelling PSB4/50	494820.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage			
Rated current			
Rated wire size	AWG 24-16	AWG 24-16	1.5 mm ²
Rated impulse voltage			8 kV
Pollution degree			3