




PTR HARTMANN

A Phoenix Mecano Company

Technical Data // FRSL4-DR

Push-In Type | Protective Conductor Clamp
3 Connections



Wire Sizes

Solid min	0.2 mm ²
Solid max	6.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	6.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	4.0 mm ²
Clamping range min	0.2mm ²
Clamping range max	6.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions


Stripped length	12.0 mm
Width	6.1 mm
Length	64.3 mm
Height TS35 x 7.5	43.0 mm

ELECTRICAL DATA

General

Cross connection channels	2
---------------------------	---

COLOURS



GREEN/YELLOW



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // FRSL4-DR

Push-In Type | Protective Conductor Clamp

3 Connections

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
FRSL4-DR-GREEN/YELLOW	43224.2	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate FAP4/3A	493421.2	20
Four-Way Covers FAD4/4/B	493427.8	20
End Stopn ZES35/2	493811.2	50
Quick Labelling PSB6/50	494702.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage			
Rated current			
Rated wire size	AWG 20-10	AWG 20-10	4.0 mm ²
Rated impulse voltage			8 kV
Pollution degree			3