



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // SMAG10/6

Screw Type | Tapping Clamp

1 Connection



Wire Sizes

Solid min	0.2 mm ²
Solid max	10.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	10.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	10.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	6.0 mm ²
Clamping range min	0.2mm ²
Clamping range max	10.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions

Stripped length	10.0 mm
Width	8.3 mm
Height	29.7 mm
Length	38.5 mm

ELECTRICAL DATA

General

Max. current	57 A
--------------	------

COLOURS

	BEIGE, similar RAL 1019
---	-------------------------



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // **SMAG10/6**

Screw Type | Tapping Clamp

1 Connection

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
SMAG10/6-BEIGE	4917122.2	10

ACCESSOIRES

Article Designation	Article Number	PU
Quick Labelling PSB8/40	499323.7	400

RATINGS

Ratings	UR	CSA	IEC
Rated voltage			800 V
Rated current			41 A
Rated wire size	AWG 22-8	AWG 22-8	10.0 mm ²
Rated impulse voltage			8 kV
Pollution degree			3