



Technical Data // SR240

Screw Type | Through Terminal Block
2 Connections



Wire Sizes

Solid min	70.0 mm ²
Solid max	240.0 mm ²
Stranded (flexible) min	70.0mm ²
Stranded (flexible) max	240.0 mm ²
Stranded (flexible) min	70.0mm ²
Stranded (flexible) max	240.0 mm ²
Stranded with ferrule min	70.0 mm ²
Stranded with ferrule max	240.0 mm ²
Two wire solid min	70.0mm ²
Two wire solid max	240.0 mm ²
Two wire with ferrule (flexible) min	95.0mm ²
Two wire with ferrule (flexible) max	240.0 mm ²
Clamping range min	70.0mm ²
Clamping range max	240.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	38.0 mm
Width	36.0 mm
Length	93.0 mm
Height TS35 x 7.5	126.3 mm
Height TS32	132.0 mm

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // SR240

Screw Type | Through Terminal Block

2 Connections

COLOURS

 BEIGE, similar RAL 1019 BLUE, similar RAL 5015 GREY, similar RAL 7004 BLACK, similar RAL 9011

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
SR240-BEIGE	41126.2	5
SR240-BLUE	41126.5	5

ACCESSOIRES

Article Designation	Article Number	PU
External Cross-Connector insulated AQ12/240	492769.2	5
External Cross-Connector insulated AQ13/240	492770.2	5
Covers AD1/240/B	492808.0	20
Einlegprofile EP240	492360.0	10
Measurement Pick-off Terminal MAG 150/240	491125.2	10
End Stopn ES35/K/ST	492828.0	50
Quick Labelling PSB6/50	494702.7	500

RATINGS

Ratings	UR	CSA	IEC
Rated voltage	600 V	600 V	1000 V
Rated current	370 A	370 A	380 A
Rated wire size	AWG 500-2/0	AWG 500-2/0	240.0 mm ²
Rated impulse voltage			8 kV
Pollution degree			3