



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // SR4-DR

Screw Type | Through Terminal Block
3 Connections



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	2.5 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	12.0 mm
Width	6.0 mm
Length	57.5 mm
Height TS35 x 7.5	47.0 mm
Height TS32	51.5 mm

ELECTRICAL DATA

General

Cross connection channels	1
Test pick off	1

COLOURS

	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015


**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // SR4-DR

Screw Type | Through Terminal Block

3 Connections

CONNECTION DIAGRAM**ORDER DATA**

Article Designation	Article Number	PU
SR4-DR-BEIGE	41210.2	100
SR4-DR-BLUE	41210.5	100

ACCESSOIRES

Article Designation	Article Number	PU
Einlegprofile EP240	492360.0	10
Insulation Plates TR51	492003.2	100
Cross-Connection uninsulated Q2	492019.0	50
Cross-Connection insulated QI2	492740.2	50
Cross-Connection uninsulated Q3	492020.0	50
Cross-Connection insulated QI3	492741.2	50
Cross-Connection uninsulated Q4	492021.0	20
Cross-Connection insulated QI4	492742.2	20
Cross-Connection uninsulated Q10	492022.0	10
Cross-Connection insulated QI10	492743.2	10
End Stopn ES35/K/ST	492828.0	50
Test Adapter TA6/1/ST	492813.0	10
Quick Labelling PSB6/50	494702.7	500

RATINGS

Ratings	UR		IEC
Rated voltage	600 V	600 V	500 V
Rated current	30 A	30 A	24 A
Rated wire size	AWG 22-12	AWG 22-12	4.0 mm ²
Rated impulse voltage			6 kV
Pollution degree			3