



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // SR4-T15-STB

Screw Type | Through Terminal Block

2 Connections



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	4.0 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	9.0 mm
Width	6.0 mm
Length	27.0 mm
Height TS15	34.5 mm

ELECTRICAL DATA

General

Cross connection channels	1
Test pick off	2

COLOURS

 BEIGE, similar RAL 1019

 BLUE, similar RAL 5015

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // SR4-T15-STB

Screw Type | Through Terminal Block

2 Connections

CONNECTION DIAGRAM**ORDER DATA**

Article Designation	Article Number	PU
SR4-T15-STB-BEIGE	41013.2	100
SR4-T15-STB-BLUE	41013.5	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate AP1.5-4	492738.2	50
Partition Plates TW1.5-4	492071.0	50
Insulation Plates TRS3	492566.2	100
Cross-Connection uninsulated Q2	492087.0	50
Cross-Connection uninsulated Q3	492088.0	50
Cross-Connection uninsulated Q4	492089.0	20
Cross-Connection uninsulated Q10	492090.0	10
End Stopn ES15	492074.2	50
Test Plug PS2.3	492007.0	20
Quick Labelling PSB6/50	494702.7	500

RATINGS

Ratings	UR	CSA	IEC
Rated voltage	300 V	300 V	500 V
Rated current	30 A	40 A	32 A
Rated wire size	AWG 22-10	AWG 22-10	4.0 mm ²
Rated impulse voltage			6 kV
Pollution degree			3