



Technical Data // SR95

Screw Type | Through Terminal Block
2 Connections



Wire Sizes

Solid min	25.0 mm ²
Solid max	95.0 mm ²
Stranded (flexible) min	25.0mm ²
Stranded (flexible) max	95.0 mm ²
Stranded (flexible) min	35.0mm ²
Stranded (flexible) max	95.0 mm ²
Stranded with ferrule min	35.0 mm ²
Stranded with ferrule max	95.0 mm ²
Two wire solid min	35.0mm ²
Two wire solid max	95.0 mm ²
Two wire with ferrule (flexible) min	50.0mm ²
Two wire with ferrule (flexible) max	95.0 mm ²
Clamping range min	25.0mm ²
Clamping range max	95.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	30.0 mm
Width	25.0 mm
Length	84.0 mm
Height TS35 x 7.5	88.5 mm
Height TS32	94.0 mm

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // SR95

Screw Type | Through Terminal Block

2 Connections

COLOURS

 BEIGE, similar RAL 1019 BLUE, similar RAL 5015 GREY, similar RAL 7004 BLACK, similar RAL 9011

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
SR95-BEIGE	41122.2	10
SR95-BLUE	41122.5	10

ACCESSOIRES

Article Designation	Article Number	PU
External Cross-Connector insulated AQ12/95	492765.2	5
External Cross-Connector insulated AQ13/95	492766.2	5
Covers AD1/95/B	492804.0	20
Einlegprofile EP95	492275.0	10
Measurement Pick-off Terminal MAG 95	491123.2	10
End Stopn ES35/K/ST	492828.0	50
Quick Labelling PSB6/50	494702.7	500

RATINGS

Ratings	UR	CSA	IEC
Rated voltage	600 V	600 V	1000 V
Rated current	230 A	230 A	232 A
Rated wire size	AWG 4/0-2	AWG 4/0-2	95.0 mm ²
Rated impulse voltage			8 kV
Pollution degree			3