

Technical Data // **SRD2.5-V-T35**

Screw Type | Through Terminal Block
4 Connections



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	2.5 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	7.0 mm
Width	5.0 mm
Length	60.2 mm
Height TS35 x 7.5	56.0 mm

ELECTRICAL DATA

General

Cross connection channels	1
Test pick off	1

COLOURS

	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015
	YELLOW, similar RAL 1023

**PTR HARTMANN**


A Phoenix Mecano Company

Technical Data // SRD2.5-V-T35

Screw Type | Through Terminal Block

4 Connections

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
SRD2.5-V-T35-BEIGE	41579.2	100
SRD2.5-V-T35-BLUE	41579.5	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate AP4	492101.2	20
Insulation Plates TRS3	492566.2	100
Cross-Connection uninsulated Q2	492567.0	50
Cross-Connection uninsulated Q3	492568.0	50
Cross-Connection uninsulated Q4	492569.0	20
Cross-Connection uninsulated Q10	492570.0	10
End Stopn ES35/K/ST	492828.0	50
Test Adapter TAD5/1/S	492821.0	10
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage	300 V	300 V	500 V
Rated current	20 A	20 A	24 A
Rated wire size	AWG 22-14	AWG 22-14	2.5 mm ²
Rated impulse voltage			6 kV
Pollution degree			3