



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // SRDT4-SB-H

Screw Type | Disconnect Terminal Block
2x2 Connections



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	2.5 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	9.0 mm
Width	8.0 mm
Length	67.0 mm
Height TS35 x 7.5	55.5 mm
Height TS32	60.0 mm

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // SRDT4-SB-H

Screw Type | Disconnect Terminal Block

2x2 Connections

COLOURS

 BEIGE, similar RAL 1019 BLUE, similar RAL 5015

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
SRDT4-SB-H-BEIGE	41383.2	50
SRDT4-SB-H-BLUE	41383.5	50

ACCESSOIRES

Article Designation	Article Number	PU
End Plate AP/SID-1	492187.2	20
External Cross-Connector insulated AQ12/8/11	492067.0	50
External Cross-Connector insulated AQ13/8/11	492068.0	50
External Cross-Connector insulated AQ14/8/11	492069.0	50
Contacthülse KH5	492470.0	1
End Stopn ES35/K/ST	492828.0	50
Quick Labelling PSB8/40	499323.7	400

RATINGS

Ratings	IEC
Rated voltage	500 V
Rated current	6.3 A
Rated wire size	AWG 22-12 4.0 mm ²
Rated impulse voltage	6 kV
Pollution degree	3