



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // SRI2.5-PNP=LED(GN)60VDC

Screw Type | Three-block Initiator Clamp

36 Connections



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	2.5 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	7.0 mm
Width	5.0 mm
Length	62.8 mm
Height TS35 x 7.5	58.3 mm
Height TS32	62.8 mm

ELECTRICAL DATA

General

Electronic components

Rated voltage DC	60 V
------------------	---------

COLOURS

	BEIGE, similar RAL 1019
---	-------------------------



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // SRI2.5-PNP=LED(GN)60VDC

Screw Type | Three-block Initiator Clamp

36 Connections

CONNECTION DIAGRAM

Bitte kontaktieren Sie unsere Vertriebsmitarbeiter.
Please contact our sales department.

ORDER DATA

Article Designation	Article Number	PU
SRI2.5-PNP=LED(GN)60VDC-BE	41274.2	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate AP2.5/I	492698.2	20
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings

Rated voltage

Rated current

Rated wire size