



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // SRM10/2

Screw Type | Through Terminal Block

4 Connections Direct mounting



Wire Sizes

Solid min	0.2 mm ²
Solid max	10.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	10.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	10.0 mm ²
Clamping range min	0.2mm ²
Clamping range max	10.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	10.0 mm
Width	8.0 mm
Height	31.0 mm
Length	32.2 mm
Length hole direct mounting	24.2 mm

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // SRM10/2

Screw Type | Through Terminal Block

4 Connections Direct mounting

COLOURS

 BEIGE, similar RAL 1019 BLUE, similar RAL 5015

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
SRM10/2-BEIGE	41500.2	50
SRM10/2-BLUE	41500.5	50

ACCESSOIRES

Article Designation	Article Number	PU
External Cross-Connector insulated AQ12/8/11	492067.0	50
External Cross-Connector insulated AQ13/8/11	492068.0	50
External Cross-Connector insulated AQ14/8/11	492069.0	50
Quick Labelling PSB8/40	499323.7	400

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage	300 V	300 V	400 V
Rated current	57 A	57 A	57 A
Rated wire size	AWG 22-8	AWG 22-8	10.0 mm ²
Rated impulse voltage			6 kV
Pollution degree			3