



**PTR HARTMANN**

A Phoenix Mecano Company

## Technical Data // SRM10/4

Screw Type | Through Terminal Block  
2 Connections With hinged lever



### Wire Sizes

|                           |                      |
|---------------------------|----------------------|
| Solid min                 | 0.2 mm <sup>2</sup>  |
| Solid max                 | 10.0 mm <sup>2</sup> |
| Stranded (flexible) min   | 0.2mm <sup>2</sup>   |
| Stranded (flexible) max   | 10.0 mm <sup>2</sup> |
| Stranded with ferrule min | 0.2 mm <sup>2</sup>  |
| Stranded with ferrule max | 10.0 mm <sup>2</sup> |
| Clamping range min        | 0.2mm <sup>2</sup>   |
| Clamping range max        | 10.0 mm <sup>2</sup> |

### Insulating Material

|                    |           |
|--------------------|-----------|
| Material           | PA 6.6    |
| Flammability class | UL 94 V-2 |

### Temperatures

|                     |              |
|---------------------|--------------|
| Working temperature | -40 - 105 °C |
|---------------------|--------------|

### Dimensions

|                             |         |
|-----------------------------|---------|
| Stripped length             | 10.0 mm |
| Width                       | 8.0 mm  |
| Height                      | 31.0 mm |
| Length                      | 48.4 mm |
| Length hole direct mounting | 40.4 mm |

**PTR HARTMANN**

A Phoenix Mecano Company

## Technical Data // SRM10/4

Screw Type | Through Terminal Block  
2 Connections With hinged lever

### COLOURS

 BEIGE, similar RAL 1019

 BLUE, similar RAL 5015

### CONNECTION DIAGRAM



### ORDER DATA

| Article Designation | Article Number | PU |
|---------------------|----------------|----|
| SRM10/4-BEIGE       | 41502.2        | 20 |
| SRM10/4-BLUE        | 41502.5        | 20 |

### ACCESSOIRES

| Article Designation                             | Article Number | PU  |
|-------------------------------------------------|----------------|-----|
| External Cross-Connector insulated<br>AQ12/8/11 | 492067.0       | 50  |
| External Cross-Connector insulated<br>AQ13/8/11 | 492068.0       | 50  |
| External Cross-Connector insulated<br>AQ14/8/11 | 492069.0       | 50  |
| Quick Labelling PSB8/40                         | 499323.7       | 400 |

### RATINGS

| Ratings               | CSA      | CSAus    | IEC                  |
|-----------------------|----------|----------|----------------------|
| Rated voltage         | 300 V    | 300 V    | 400 V                |
| Rated current         | 57 A     | 57 A     | 57 A                 |
| Rated wire size       | AWG 22-8 | AWG 22-8 | 10.0 mm <sup>2</sup> |
| Rated impulse voltage |          |          | 6 kV                 |
| Pollution degree      |          |          | 3                    |