


Technical Data // SRMB2.5/2

Screw Type | Through Terminal Block

4 Connections Direct mounting



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	2.5 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	7.0 mm
Width	5.0 mm
Height	23.0 mm
Length	24.5 mm
Length hole direct mounting	17.4 mm

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // SRMB2.5/2

Screw Type | Through Terminal Block

4 Connections Direct mounting

COLOURS

 BEIGE, similar RAL 1019 BLUE, similar RAL 5015

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
SRMB2.5/2-BEIGE	41321.2	50
SRMB2.5/2-BLUE	41321.5	50

ACCESSOIRES

Article Designation	Article Number	PU
External Cross-Connector insulated AQ12/5/11	492032.0	50
External Cross-Connector insulated AQ13/5/11	492033.0	50
External Cross-Connector insulated AQ14/5/11	492044.0	10
External Cross-Connector insulated AQ110/5/11	492045.0	10
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	UR		IEC
Rated voltage	300 V	300 V	400 V
Rated current	20 A	20 A	24 A
Rated wire size	AWG 22-12	AWG 22-12	2.5 mm ²
Rated impulse voltage			6 kV
Pollution degree			3