



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // SRMB4/14-FW1-14B

Screw Type | Through Terminal Block

28 Connections Direct mounting With labelling on both sides



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	4.0 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	9.0 mm
Width	6.0 mm
Height	23.0 mm
Length	99.7 mm
Length hole direct mounting	92.6 mm

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // SRMB4/14-FW1-14B

Screw Type | Through Terminal Block

28 Connections Direct mounting With labelling on both sides

COLOURS

 BEIGE, similar RAL 1019 BLUE, similar RAL 5015

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
SRMB4/14-FW1-14B-BEIGE	42352.2	20
SRMB4/14-FW1-14B-BLUE	42352.5	20

ACCESSOIRES

Article Designation	Article Number	PU
External Cross-Connector insulated AQ12/6/11	492125.0	50
External Cross-Connector insulated AQ13/6/11	492126.0	50
External Cross-Connector insulated AQ14/6/11	492140.0	10
External Cross-Connector insulated AQ110/6/11	492141.0	10

RATINGS

Ratings	UR	CSA	IEC
Rated voltage	300 V	300 V	400 V
Rated current	30 A	25 A	32 A
Rated wire size	AWG 22-12	AWG 22-12	4.0 mm ²
Rated impulse voltage			6 kV
Pollution degree			3