



Highlights

1 to 24 poles

Vertical pin strip

Spacing 5.08 mm

Closed ends

Wire Sizes

Solid min -

Solid max -

Stranded (flexible) min -

Stranded (flexible) max -

Stranded with ferrule min -

Stranded with ferrule max -

Dimensions

PCB hole diameter 1.4 mm

Materials

Contact pin Copper Alloy

Insulating Material

Material PA 6.6

Flammability class UL 94 V-0

Temperatures

Operating temperature (without mech. load) -40 °C - 105 °C

Store temperature -40 °C - 105 °C

Wave Soldering Process

Soldering temperature, recommended 260 °C

Peak soldering time, recommended 3-4 s

Reflow Process

Soldering temperature, recommended -

Peak soldering time, recommended -

Spacing 5.08 mm

Colours

GREEN, RAL 6018

BLACK, RAL 9011

BASALT GREY, RAL 7012

PEBBLE GREY, RAL 7032

LIGHT GREY, RAL 7035

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
 Special colours on request.

Ratings

				
UseGroup	B	C	D	
Rated voltage	300 V	150 V	300 V	250 V
Rated current	15 A	15 A	10 A	12 A
Overvoltage category				III
Test voltage	1.60 kV	1.30 kV	1.60 kV	4.0 kV
Pollution degree				3


Counterparts (Spacing 5.08 mm)

Pin Strip/Terminal Block

STLZ950-INV	AKZ950	AKZ955	AKZ1100	AKZ1110	AKZ1200	AKZ4951
-------------	--------	--------	---------	---------	---------	---------

In combination of connectors with different admission data, the lower value is valid.

Accessoires

Figure	Designation	Article Number
	Coding Star CS2-5.0/5.08-RED	Order Data: 50000000024
	Separating Element SE-STL950-GREEN	Order Data: 50950000002

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // STLZ950/..G-5.08-V-GREEN

Spacing 5.08 mm

Order Data (Spacing 5.08 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	11.36	STLZ950/2G-5.08-V-GREEN	50950025121 F	200
3	16.44	STLZ950/3G-5.08-V-GREEN	50950035121 F	200
4	21.52	STLZ950/4G-5.08-V-GREEN	50950045121 F	200
5	26.60	STLZ950/5G-5.08-V-GREEN	50950055121 E	100
6	31.68	STLZ950/6G-5.08-V-GREEN	50950065121 E	100
7	36.76	STLZ950/7G-5.08-V-GREEN	50950075121 E	100
8	41.84	STLZ950/8G-5.08-V-GREEN	50950085121 D	50
9	46.92	STLZ950/9G-5.08-V-GREEN	50950095121 D	50
10	52.00	STLZ950/10G-5.08-V-GREEN	50950105121 D	50
11	57.08	STLZ950/11G-5.08-V-GREEN	50950115121 D	50
12	62.16	STLZ950/12G-5.08-V-GREEN	50950125121 D	50
13	67.24	STLZ950/13G-5.08-V-GREEN	50950135121 D	50
14	72.32	STLZ950/14G-5.08-V-GREEN	50950145121 D	50
15	77.40	STLZ950/15G-5.08-V-GREEN	50950155121 D	50
16	82.48	STLZ950/16G-5.08-V-GREEN	50950165121 D	50
17	87.56	STLZ950/17G-5.08-V-GREEN	50950175121 D	50
18	92.64	STLZ950/18G-5.08-V-GREEN	50950185121 D	50
19	97.72	STLZ950/19G-5.08-V-GREEN	50950195121 D	50
20	102.80	STLZ950/20G-5.08-V-GREEN	50950205121 D	50
21	107.88	STLZ950/21G-5.08-V-GREEN	50950215121 D	50
22	112.96	STLZ950/22G-5.08-V-GREEN	50950225121 D	50
23	118.04	STLZ950/23G-5.08-V-GREEN	50950235121 D	50
24	123.12	STLZ950/24G-5.08-V-GREEN	50950245121 D	50



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // **STLZ950/..G-5.08-V-GREEN**

Spacing 5.08 mm

Technical drawing

