

Technical Data

// ZRS2.5-1LS1RS

Multi-Connector Tension Spring Type | Through Terminal Block

2 Connections



Wire Sizes	
Insulating Material	
Material	PA 6.6
Flammability class	UL 94 V-0
Temperatures	
Working temperature	-40 - 120 °C
Dimensions	
Width	5.1 mm
Height	38.5 mm
Length	54.0 mm
Height TS35 x 7.5	39.5 mm
ELECTRICAL DATA	
General	
Cross connection channels	2
COLOURS	
	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015
	ORANGE, similar RAL 2003

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // ZRS2.5-1LS1RS

Multi-Connector Tension Spring Type | Through Terminal Block

2 Connections

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
ZRS2.5-1LS1RS-BE	43655.2	100
ZRS2.5-1LS1RS-BLUE	43655.5	100
ZRS2.5-1LS1RS-ORANGE	43655.3	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate ZAPS2.5/2S	493691.2	50
Cross-Connection insulated ZQI2.5/2	493710.8	50
Cross-Connection insulated ZQI2.5/3	493711.8	50
Cross-Connection insulated ZQI2.5/4	493712.8	20
Cross-Connection insulated ZQI2.5/5	493713.8	20
Cross-Connection insulated ZQI2.5/6	493714.8	20
Cross-Connection insulated ZQI2.5/7	493715.8	20
Cross-Connection insulated ZQI2.5/8	493716.8	10
Cross-Connection insulated ZQI2.5/9	493717.8	10
Cross-Connection insulated ZQI2.5/10	493718.8	10
Cross-Connection insulated ZQI2.5/0.5/99	493719.8	1
Test Adapter ZTA2.5	493740.2	10
End Stopn ZES35/2	493811.2	50
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	UR	CSA	IEC
Rated voltage	300 V	300 V	500 V
Rated current	20 A	20 A	24 A
Rated wire size			
Rated impulse voltage			8 kV
Pollution degree			3