

Technical Data // ZRSL10

Tension Spring Type | Protective Conductor Clamp
2 Connections



Wire Sizes

Solid min	1.5 mm ²
Solid max	16.0 mm ²
Stranded (flexible) min	1.5mm ²
Stranded (flexible) max	16.0 mm ²
Stranded (flexible) min	1.5mm ²
Stranded (flexible) max	10.0 mm ²
Stranded with ferrule min	1.5 mm ²
Stranded with ferrule max	10.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions


Width	10.1 mm
Length	73.5 mm
Height TS35 x 7.5	50.5 mm

ELECTRICAL DATA

General

Test pick off	2
---------------	---

COLOURS



GREEN/YELLOW



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // ZRSL10

Tension Spring Type | Protective Conductor Clamp

2 Connections

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
ZRSL10-GREEN/YELLOW	43598.2	50

ACCESSOIRES

Article Designation	Article Number	PU
End Plate ZAP10/2A	493788.2	20
Four-Way Covers ZAD10/4/B	493709.0	20
End Stopn ZES35	493748.2	50
Test Adapter ZTA10	493790.2	10
Quick Labelling PSB8/40	499323.7	400

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage			
Rated current			
Rated wire size	AWG 16-6	AWG 16-6	10.0 mm ²
Rated impulse voltage			8 kV
Pollution degree			3