



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // ZRSL2.5-N-T15-DR

Tension Spring Type | Protective Conductor Clamp

3 Connections



Wire Sizes

Solid min	0.5 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.5mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.5 mm ²
Stranded with ferrule max	2.5 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions


Width	5.1 mm
Length	52.5 mm
Height TS15	34.0 mm
Height TS15 with labelling adapter	44.0 mm

ELECTRICAL DATA

General

Cross connection channels	1
Test pick off	2

COLOURS



GREEN/YELLOW



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // ZRSL2.5-N-T15-DR

Tension Spring Type | Protective Conductor Clamp

3 Connections

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
ZRSL2.5-N-T15-DR-GREEN/YELLOW	43601.2	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate ZAP-SR-3A/15	493794.2	50
Four-Way Covers ZAD2.5/4/B	493706.0	20
Four-Way Covers ZAD4/4/B	493707.0	20
Test Adapter ZTA2.5	493740.2	10
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage			
Rated current			
Rated wire size	AWG 20-12	AWG 20-12	2.5 mm ²
Rated impulse voltage			8 kV
Pollution degree			3