



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // ZRSL4

Tension Spring Type | Protective Conductor Clamp

2 Connections



Wire Sizes

Solid min	0.5 mm ²
Solid max	6.0 mm ²
Stranded (flexible) min	0.6mm ²
Stranded (flexible) max	6.0 mm ²
Stranded with ferrule min	0.5 mm ²
Stranded with ferrule max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions


Width	6.1 mm
Length	64.0 mm
Height TS35 x 7.5	42.0 mm

ELECTRICAL DATA

General

Test pick off	2
---------------	---

COLOURS



GREEN/YELLOW



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // ZRSL4

Tension Spring Type | Protective Conductor Clamp

2 Connections

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
ZRSL4-GREEN/YELLOW	43525.2	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate ZAP4/2A	493703.2	50
Four-Way Covers ZAD4/4/B	493707.0	20
End Stopn ZES35	493748.2	50
Test Adapter ZTA4	493741.2	10
Quick Labelling PSB6/50	494702.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage			
Rated current			
Rated wire size	AWG 20-10	AWG 20-10	4.0 mm ²
Rated impulse voltage			8 kV
Pollution degree			3