



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // ZRSLID2.5

Tension Spring Type | Protective Conductor Clamp

6 Connections



Wire Sizes

Solid min	0.5 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.5mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.5 mm ²
Stranded with ferrule max	2.5 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions


Width	5.1 mm
Length	116.2 mm
Height TS35 x 7.5	68.0 mm

ELECTRICAL DATA

General

Test pick off	6
---------------	---

COLOURS



GREEN/YELLOW

**PTR HARTMANN**


A Phoenix Mecano Company

Technical Data // ZRSLID2.5

Tension Spring Type | Protective Conductor Clamp

6 Connections

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
ZRSLID2.5-GREEN/YELLOW	43593.2	50

ACCESSOIRES

Article Designation	Article Number	PU
End Plate ZAP2.5/ID	493761.2	20
Four-Way Covers ZAD2.5/4/B	493706.0	20
Labelling Adapters ZBA3	493813.2	50
End Stopn ZES35	493748.2	50
Test Adapter ZTA2.5	493740.2	10
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage			
Rated current			
Rated wire size	AWG 20-12	AWG 20-12	2.5 mm ²
Rated impulse voltage			6 kV
Pollution degree			3