

Technical Data // ZRSLM2.5-RC

Tension Spring Type | Through Terminal Block
2 ConnectionsDirect mountingWith snap-in clip - black/yellow version



Wire Sizes

Solid min	0.5 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.5mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.5 mm ²
Stranded with ferrule max	2.5 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions

Width	5.1 mm
Height	24.0 mm
Length	40.0 mm

ELECTRICAL DATA

General

Cross connection channels	1
Test pick off	2

COLOURS



BLACK/YELLOW



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // ZRSLM2.5-RC

Tension Spring Type | Through Terminal Block

2 Connections Direct mounting With snap-in clip - black/yellow version

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
ZRSLM2.5-RC-BLACK/YELLOW	43639.2	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate ZAP-SR/RC	493758.2	50
Cross-Connection insulated ZQI2.5/2	493710.8	50
Cross-Connection insulated ZQI2.5/3	493711.8	50
Cross-Connection insulated ZQI2.5/4	493712.8	20
Cross-Connection insulated ZQI2.5/5	493713.8	20
Cross-Connection insulated ZQI2.5/6	493714.8	20
Cross-Connection insulated ZQI2.5/7	493715.8	20
Cross-Connection insulated ZQI2.5/8	493716.8	10
Cross-Connection insulated ZQI2.5/9	493717.8	10
Cross-Connection insulated ZQI2.5/10	493718.8	10
Cross-Connection insulated ZQI2.5/0.5/99	493719.8	1
Four-Way Covers ZAD2.5/4/B	493706.0	20
Four-Way Covers ZAD4/4/B	493707.0	20
Test Adapter ZTA2.5	493740.2	10
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage			
Rated current			
Rated wire size	AWG 20-12	AWG 20-12	2.5 mm ²
Rated impulse voltage			8 kV
Pollution degree			3