



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // ZTR2.5-DRL-ST

Tension Spring Type | Disconnect Terminal Block
4 Connections



Wire Sizes

Solid min	0.5 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.5mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.5 mm ²
Stranded with ferrule max	2.5 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions

Width	5.1 mm
Length	92.4 mm
Height TS35 x 7.5	57.1 mm

ELECTRICAL DATA

General

Cross connection channels	1
Test pick off	2

COLOURS

	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // ZTR2.5-DRL-ST

Tension Spring Type | Disconnect Terminal Block

4 Connections

CONNECTION DIAGRAM**ORDER DATA**

Article Designation	Article Number	PU
ZTR2.5-DRL-ST-BEIGE	43608.2	100
ZTR2.5-DRL-ST-BLUE	43608.5	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate ZAPT2.5/4A	493798.2	20
Cross-Connection insulated ZQI2.5/2	493710.8	50
Cross-Connection insulated ZQI2.5/3	493711.8	50
Cross-Connection insulated ZQI2.5/4	493712.8	20
Cross-Connection insulated ZQI2.5/5	493713.8	20
Cross-Connection insulated ZQI2.5/6	493714.8	20
Cross-Connection insulated ZQI2.5/7	493715.8	20
Cross-Connection insulated ZQI2.5/8	493716.8	10
Cross-Connection insulated ZQI2.5/9	493717.8	10
Cross-Connection insulated ZQI2.5/10	493718.8	10
Cross-Connection insulated ZQI2.5/0.5/99	493719.8	1
Four-Way Covers ZAD2.5/4/B	493706.0	20
End Stopn ZES35	493748.2	50
Test Adapter ZTA2.5	493740.2	10
Disconnect Plug ZDS1/ZTR	493612.2	20
Disconnect Plug ZDS2/ZTR	493613.2	20
Disconnect Plug ZDS3/ZTR	493614.2	20
Disconnect Plug ZDS4/ZTR	493615.2	20
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	IEC
Rated voltage	400 V
Rated current	18 A
Rated wire size	2.5 mm ²
Rated impulse voltage	6 kV
Pollution degree	3